ANGELTRAX

Service Notice #16-04



ANGELTRAX SOLID-STATE DRIVES

Voluntary Product Replacement

AngelTrax, a leading provider of mobile video surveillance solutions, is replacing all HDD500ST and HDD500ST-PF solid-state drives due to performance malfunctions and in fulfillment of the AngelTrax 10-year full replacement warranty on solid-state drives. Each solid-state drive with model number HDD500ST or HDD500ST-PF will be replaced with an acceptable solid-state drive that has been thoroughly tested and approved for operation.

If you have purchased an AngelTrax solid-state drive with model number HDD500ST or HDD500ST-PF, please contact the AngelTrax Technical Support Department at 1-800-673-1788 for replacement.

ALL of our Service Updates can be found on the New York Bus Sales website

Or at the New York Head Mechanic website







AngelTrax Solid-State Hard Drive

BOOST SYSTEM PERFORMANCE

Engineered with no moving parts, each Angelfrax solid state hard drive is more reliable and more durable than a traditional hard drive operating with a spinning disk. The SSD features faster, cook ripperation for greater energy efficiency.

SSD FEATURES

- Boot un system in seconds'
- No Moving Parts More durable and reliable than traditional hard drive that use a spinning disk
- Less Power Consumption More are rgy ethicient and runs cooler compared to traditional hand drives
- Supports tile encryption
- user selectable gassword (# BIOS suggorted)
- Secure erase (factory reset + AFA)
- Early Bad Block Reffrement Improves the lifetime of the SSD by ensuring that weak blocks are retired.
- TRIM Support Prolongs SSD gertormance over time!
- ECC Protection Avoids errors and gromotes stability during data reads/wires
- S.M.A.R.T. Self-Monkoring, Analysis and Reporting Fechnology monkoring system that detects and reports on various indicators of drive reliability, with the line of of enabling the anticination of hardware failures.
- DataRetresh, DevSIp. Temperature Sensor and more
- 10 yearfull replacement warranty

# 10ugg#	CAPACIFE	READ WE/S	WRITE ME/S	1075 (READ)	IGPS (WRITE)
40025631	250G5	560 VIS	915416	72.000	79.000
40050031	5 600 5	560 WE	460WS	74.000	76,000
40011631	rre	560 WE	46046	76,000	76,000

*OScar kar cupp or required



DIMENSIONS & WEIGHT

- Height: 0.28 inches
- Width: 2.75 inches
- Depth: 5.94 inches
- Weight: 0.12 goulds

AVAILABLE GAPACITIES

- 250GB
- 500GB
- 1 FB

TECH SPECS

- Form Factor: 2.5 1, 28 inches neight.
- Connectivity: SAFA SGD/s (packwards compatible with SAFA 3G b/s and SAFA 1.5G b/s)
- DDR3 External DRAM
- Use r-upg ra de able 1 ir mwa re
- TAA . RoHS. FCC . C.E. and WWN compliant
- Power Consumption: 2W (active), 0.7W (alle)
- Flash Type: MilC (sync)
- Operating Temperature: 32°F - 198°F (0°C - 70°C)
- 510 rage Temperature:
- -40°F 185°F (-40°C 85°C)
- MTBF: 1,500,000 hours
- Shock Resistance: ISOOG

11/2015 - Specifications, features and applications of use are subject to change without notice.



ALL of our Service Updates can be found on the New York Bus Sales website

Or at the New York Head Mechanic website







CONTACT OUR SERVICE OR PARTS DEPARTMENT WITH ANY QUESTIONS

SERVICE

Chittenango: 800-962-5768 Daryl Wallace or Brian Lamaitis

Rochester: 800-463-3232 Dave Schaub Albany: 866-867-1100 Ben Reiling

Warranty: 800-962-5768

Morgan Jenkins
Customer Service
Representatives

Eastern Region:

Gary Bigness 845-500-3707

Central Region:

JJ Richmond 315-559-3999

Western Region:

Mike Panzica 716-908-3186 **PARTS**

Director of Parts

Jim Hogan

jhogan@newyorkbussales.com

607-227-5794

Chittenango: 800-962-5768

Gari McQuade

gmcquade@newyorkbussales.com

Bill Cox

bcox@newyorkbussales.com

John Lewin

jlewin@newyorkbussales.com

Dave Grant

dgrant@newyorkbussales.com

Albany: 866-867-1100

Sean Conway

sconway@newyorkbussales.com

John Green

jgreen@newyorkbussales.com

Rochester: 800-463-3232

Dave Cook

dcook@newyorkbussales.com

Steve Hibbard

shibbard@newyorkbussales.com

ALL of our Service Updates can be found on the New York Bus Sales website

Or at the New York Head Mechanic website





